



### Power Relay Output Module

#### Features

- PoE and Regular Ethernet Options
- Built-In Web Server
- Web HMI
- Modbus/TCP, Modbus/UDP Protocol
- Communication Security
- Dual Watchdog
- Operating Temperature: -25 ~ +75 °C
- I/O Pair Connection
- Built-In I/O
- Power Relay: 8 Channels

### Introduction

The ET-7000/PET-7000, a web-based Ethernet I/O module, features a built-in web server which allows configuration, I/O monitoring and I/O control by simply using a regular web browser. Remote control is as easy as surfing the Internet.

Besides, with the web HMI function, no more programming or HTML skills are required; creating dynamic and attractive web pages for I/O monitoring and I/O control would be fun to engineers ever after. The ET-7000/PET-7000 offers easy and safe access for users from anytime and anywhere! In addition, the ET-7000/PET-7000 also supports Modbus/TCP protocol that makes perfect integration to SCADA software.

Furthermore, PET-7000 features "PoE" that not only data but also power is carried through an Ethernet cable. This feature makes installation of PET-7000 a piece of cake. Imagine that no more unnecessary wires, only an Ethernet cable takes care of everything in the field.

### Applications

Building Automation, Factory Automation, Machine Automation, Remote Maintenance, Remote diagnosis, Testing Equipment.


### System Specifications

Models	ET-7067	PET-7067
<b>Software</b>		
Built-In Web Server	Yes	
Web HMI	Yes	
I/O Pair Connection	Yes	
<b>Communication</b>		
Ethernet Port	10/100 Base-TX with Auto MDI/MDI-X	
Protocol	Modbus/TCP, Modbus/UDP	
Security	ID, Password and IP Filter	
Dual Watchdog	Yes, Module (0.8 second), Communication (Programmable)	
<b>LED Indicators</b>		
L1 (System Running)	Yes	
L2 (Ethernet Link/Act)	Yes	
L3 (Ethernet 10/100 M Speed)	Yes	
PoE Power	-	Yes
<b>2 Way Isolation</b>		
Ethernet	1500 V <sub>oc</sub>	-
I/O	3000 V <sub>rms</sub>	3000 V <sub>rms</sub>
<b>EMS Protection</b>		
ESD (IEC 61000-4-2)	4 kV Contact for each terminal	
EFT (IEC 61000-4-4)	+/-2 kV for Power	
<b>Power Requirements</b>		
Reverse Polarity Protection	Yes	
Powered from terminal block	Yes, 10 ~ 30 V <sub>oc</sub>	Yes, 12 ~ 48 V <sub>oc</sub>
Powered from PoE	-	Yes, IEEE 802.3af, Class1
Consumption	3.2 W	5.3 W
<b>Mechanical</b>		
Dimensions (W x L x D)	72 mm x 123 mm x 35 mm	
Installation	DIN-Rail or Wall mounting	
<b>Environment</b>		
Operating Temperature	-25 °C ~ +75 °C	
Storage Temperature	-30 °C ~ +80 °C	
Humidity	10 ~ 90% RH, non-condensing	


### I/O Specifications

Power Relay		
Output Channels	8	
Type	Power Relay, Form A (SPST N.O.)	
Operating Voltage Range	250 V <sub>AC</sub> /30 V <sub>DC</sub>	
Max. Load Current	5.0A/channel at 25 °C	
Operate Time	6 ms (Typical)	
Release Time	3 ms (Typical)	
Electrical Life (Resistive Load)	VDE	5A 250 V <sub>AC</sub> 30,000 ops (10 ops/minute) at 75 °C 5A 30 V <sub>DC</sub> 70,000 ops (10 ops/minute) at 75 °C
	UL	5A 250 V <sub>AC</sub> /30 V <sub>DC</sub> 6,000 ops. 3A 250 V <sub>AC</sub> /30 V <sub>DC</sub> 100,000 ops.
		Mechanical Life
Power On Value	Yes, Programmable	
Safe Value	Yes, Programmable	

### Pin Assignment



### Wire Connection



### Ordering Information

ET-7067 CR	8-channel Power Relay Output Module (RoHS)
PET-7067 CR	8-channel Power Relay Output Module PoE Module (RoHS)

### Accessories

NS-205 CR	Unmanaged 5-port Industrial Ethernet Switch; requires 24 V <sub>DC</sub> Input (RoHS)
NS-205PSE CR	Unmanaged Ethernet switch with 4-PoE and 1 RJ45 uplink; requires 48 V <sub>DC</sub> Input (RoHS)
NS-205PSE-24V CR	Unmanaged Ethernet switch with 4-PoE and 1 RJ45 uplink; requires 24 V <sub>DC</sub> Input (RoHS)
MDR-20-24 CR	24V/1A, 24 W Power Supply with DIN-Rail Mounting (RoHS)
DIN-KA52F-48 CR	48V/0.52A, 25 W Power Supply with DIN-Rail Mounting (RoHS)