

Orchestrator



Version 4.5.0 Release Information

Version 4.5

of the Orchestrator Software has now been released.

Version 4.5 contains the following fixes/changes from V4.0

Tested and supported the following platforms:

32 and 64 bit Windows 8

32 and 64 bit Windows 7

32 and 64 bit Windows Vista

32 and 64 bit Windows Server 2008

Windows XP

Windows Server 2003

Windows 2000

Above platforms on Virtual PC, Sun Virtual Box and VMware

Changes

Operating System: Tested and supported the following platforms:

32 and 64 bit Windows 8

32 and 64 bit Windows 7

32 and 64 bit Windows Vista

32 and 64 bit Windows Server 2008

Windows XP

Windows Server 2003

Windows 2000

Above platforms on Virtual PC, Sun Virtual Box and VMware

- Clients: New Product Replay client for trends, data export and enter text logs
 Monitor and Replay client licences
- New Add-on: Site to Office Replication (mirror server systems to central database & allow data access to central db, rather than individual servers.
- New Add-on: Web Service (to run Client licences across the internet)
- New Product Gas Chromatograph processor
- General: Digital signing of exes and dlls for compatibility of virus scanners
- General: Update Sentinel Superpro driver libraries to 7.1
- Driver: New Novolec, Sartorius, Fluke, AMS, Digiplan, GASM, Pumpworks, VPRO Driver
- Calculator: Calculator Number of Scans and Activity Logger Functions
- Alarm Annunciator: Alarm SMS Annunciator for GSM and 3G Modems
- Alarm Monitor: Alarm and Warning duration in alarm monitor, logger and printer
- Logger: Substituting of TeamViewer ID Skype User and Computer Name and Lock Code in Logger Text

- Calculator: Updating of channel text including Channel values TeamViewer ID Skype User and Computer Name and Lock Code in Calculator
- Configurable Monitor: Including Channel values TeamViewer ID Skype User and Computer Name and Lock Code in Configurable Monitor command lines
- Monitors: Channel and Configurable Monitor from Live Log Directories and Databases
- Configurable Monitor: Parameter for prompting Selection of Server on startup of configurable monitor
- Configurable Monitor: Support for relative path configurable monitor command line parameters
- Trends:- Trends refresh of rewritten logged data
- Trends: Speeding up of test for new log files in directories in trends
- Trends: Override value precision display for individual channels in trends
- Data Export: Data export to local temporary files followed by file copy to speed up export process
- New Driver: Fardux IDEA Logger Driver
- Driver: HP Agilent VISA Addressing for USB&Ethernet 34972A and Interactive Send Command
- Logger:- Relative Paths for User Defined Log Directories
- Logger: Manual inputs no longer update text logs or cause a refresh
- Logger: Indicator of scan sizes on channels tab of standard logger configuration
- History Channels: Recording of history channels by channel value (eg depth)

- Calculator: Calculator lockup controlling logger on system disable
- Configurable Monitor: Configurable Monitor shifts objects if resolution is too great
- Configurable Monitor: Configurable Monitor does not provide Horizontal Scrolling if objects do not fit onto current screen size
- Configurable Monitor: Buttons are not rounded on non-white backgrounds in configurable monitor
- General: Import not working and incorrect display of floating values with comma decimal separator
- General: Orchestrator TCP-IP port switched on by default creating vulnerability if firewall is switched off
- General: HASP and Sentinel Driver conflicts avoided by uninstalling unused driver during install
- General: On CORAL, XPacSDK dll loaded from WINDOWS directory
- General: Occasional 64-bit Windows 7 crash of service.exe
- Data Export: Data export of elapsed time in .dif format creates invalid .dif file
- Data Export: Alignment of headers on tab and text output files
- Data Export: No Excel output file if template checked but no template file selected in Data Export
- Logger: Cycle on event logger does not create a new file if a new event occurs during post event logging
- Logger: UTC Database Registry setting caused logger to not start
- Logger: Start and Stop times or the file name should not change if a different configuration is selected.
- Logger: Enter text log not available in trends if no predefined text entries for the logger
- Logger: No rename of log files on exit from trends, data export and enter text logs with stop times on files
- Drivers: Modbus Slave restart Issue- Failed to Open Port 502 (0)

- **Drivers:** PSI 9000 Series Driver Import of Channel Configuration does not import unit channel greater than 9.
- **Drivers:** HP Agilent driver error on RTD channels
- Drivers: Exter_nt and wellbore.ocx not included in setups
- Drivers: Ext (internal) CJC not working on Agilent 3497XA Driver
- Drivers: Environcon scanner crash when less than 1000 analog and 560 digitals specified in devcap
- Drivers: Scanivalve DSA 3215 reporting scans in multple packets
- WITS: WITSML driver not working through proxy servers.
- WITS: WITS Inputs handling of RST TCP packets
- WITS: WITSML Driver Lock Up when Invalid User Name or Password specified

Version 4.0 contains the following fixes/changes from V3.3

Changes

- Operating System:
 - Supports Windows 7, Vista, XP, Server 2008 (32 and 64-bit) Supports Server 2003, Windows 2000
 - Above platforms on Virtual PC, Sun Virtual Box and VMware
- Operating System: Dual Server and Client Functionality on Higher Level Servers
- General: Export Image from command line for trend and monitor bitmaps on websites
- General: Document ActiveX control. Trends and Alarm Monitor in Configurable Monitor.
- General: Single Remote Desktop Client Allowed onto Server on Single User Remote Desktop Platforms e.g. CORAL
- General: Client Software Key Licensing on Windows Server Platforms
- General: Sharing of trend and configurable monitor documents
- General: User supplied product.reg files on setups for user registry settings
- General: Support for HASP HL Keys including network keys
- General: Registry Option to store Digital Channel State as Text in Databases Logs
- General: Registry Option to store Date/Time in UTC Format in Database Logs
- Configurable Monitor: New set of Instrumentation Controls in Configurable Monitor
- Configurable Monitor: Configurable Monitor Time Offset
- Configurable Monitor: Export Image facility
- Data Export: Configuration Files, Channel Lists, Additional Content Options and Excel
- Data Export: Channel Tag Description Lines and Date Time Format in Data Export
- Calculator: Calculator Scale and Offset and Assign to Channel Range
- Trends: Enter Text Log Replay Facility
- Trends: Vertical Trends with Track Options for Multiple X-Axis
- Trends: Enter Start-End Period in Trends
- Trends: Trends recovery from disconnect of network files
- Trends: Autoscale trend lines from channel configuration
- Drivers: Instrunet Driver compatible with i4xx Series cards
- Drivers: ICP DCON I87K Series Driver and XPAC support
- Drivers: Imp Module Range and Mode
- Drivers: Lakeshore 218 340 and 370 Driver
- Drivers: Agilent 5700 and 6033 Power Supply Driver
- Drivers: Computerboards AUXPORT in Channels 1-8 if 8 digital channels defined in devcap.txt

- Drivers: WITS Input Source IP Address and Alphanumeric Record Items in Digital Channels
- Drivers: Log records support in WITSML driver
- Drivers: Support for 3595 4U USB Interface in Imp Driver
- Drivers: Kvaser CANBus Driver
- PID: Programmable Scale and Offset on PID Controller
- User Library: Support for C# in User Library
- User Library: Remote Calls in User Library

- General: Exported images need to be stored in a standard directory
- Logging: Append mode loggers create new log files when Trends are connected to active log file
- Logging: Logger directory names generated by digital channels containing forward or back slash in current values caused errors
- Alarm Annunciator: SMS annunciator can't open Com ports higher than Com 9
- Channel Monitor: Crashes when trying to connect to a device with a print name longer than 16 characters
- Configurable Monitor: Does not recover from connection failure in Internet Client mode
- Trends: Auto opens file instead of file selected on launch
- Trends: Header Logo is not shown in correction position when Trends documents are printed
- Trends: Print Preview of Trends Incorrectly positions items
- Trends: Crashing on replaying from live log files using mapped network drives
- Trends: Text logged to database not displayed in Trends
- Trends: Fails to Auto Pan if Active for longer than 24 hours
- Data Export: Append option displayed on automatic export to DIF files
- OPC Server: Data Access 2.0 Client produces error on connection to OPC Server
- Drivers: Reconfigure of Modbus master connected to a slave causes Can't initialise device error
- Drivers: Climet driver can't read configuration if more than one Climet is installed
- Drivers: Instrunet Driver Logging when Achieved Sample Rate Slower than 1kHz
- Drivers: ICP DCON 7080 Counter Frequency Channel Configuration
- Drivers: Debug window appears when Dataweb driver is enabled
- Drivers: Can't change board number on GE Druck Pressure Device

Version 3.3 contains the following fixes/changes from V3.1

Changes

- **General**: Supports client/server operation over TCP/IP without file sharing Supports Windows Vista, XP, 2003 and 2000 and Virtual PC.
- General: Support for SQL Server 2005 Replication
- General: Licensing of Versions, number of Drivers and I/O count
- General: Licensing on Virtual PC and Terminal Services
- General: Help Converted from WinHelp to HTMLHelp for Vista
- General: Windows XP Look and Feel
- General: Visual Studio 2005 Support
- General: Current Config Directory Purge
- General: Multiple User Channel Processors
- General: Last selected sever in configurable monitor navigation command and in trends most recent open
- General: Headers on Channel Configuration Export and Import
- Alarm System : Alarm Acknowledgement Comments
- Calculator: Calculator Array Access
- Logger: Rate of Change Logger Rewind Threshold
- Internet Server: Improved Deployment and Operation of Internet Client
- Trends Value Entry
- Trends Logo
- Trends Export Image
- Trends Axis on Right Hand Side and Clicking
- Trends Text on Graph with Edit and Position
- Trends Log Scaling
- Drivers: WITS Input and Output Drivers
- Drivers : WITSML Driver
- Drivers : Climet Particle Counter Driver
- Drivers: Changes to Generic RS-232 Driver for Lawicel CAN Bus 232 Converter.doc
- Drivers: Modbus driver timeout in milliseconds
- Drivers: Additional Columns on Agilent and Yokogawa Channel Configuration Export and Import
- Drivers: Additional Columns on Intercole Spectra and PSI 9000 Series Configuration
 Export and Import
- Drivers: GE Druck Pressure Indicator 142/150 Driver
- Drivers: ICP DCON 7000 Series Driver
- Configurable monitor: Edit, List and checkbox forms controls
- Configurable monitor : Data Source and Properties of multiple objects
- Configurable monitor : Confirmation on toggles and navigation buttons
- PID: Setpoint change no longer resets error term and provides for output calculation
- Sentinel Protection System : Installation

- **General:** Log file merge displays wrong product name in title bar
- General: Incorrect Icon appears on Start Menu for Client Install
- Configurable monitor: Client Logging in Config Mon ignores Poll Rate
- Configurable monitor: Configurable Monitor crashes when trying to paste the selector control
- Configurable monitor: Assigning function keys in Configurable Monitor doesn't enable Save button
- Configurable monitor : Pressing space bar causes a crash in Configurable Monitor when no objects are selected
- Calculator: Calculator triggers too many updates
- Calculator: Long formulae in the calculator cause the Calculator to crash
- Calculator: Timers reset to zero after a reconfigure
- Datascan Driver: Intermittent errors on Datascan 10Hz configuration with handshaking disabled
- Datascan Driver: Datascan channels display error when a comma is used in the tag
- Datascan Driver: 7X27 Modules In Single Shot with Continuous Controller Mode
- Datascan Driver: Datascan Configuration causes error when opened from a client
- Trends: Helv font not available in fonts list in trends
- Trends: Text logs entered while in XY mode are logged with a date in 1970
- Trends: Trends give an error when printing with logged text and header turned on
- Trends: Pan right doesn't work after zoom left on sample skip
- Trends: Axis labels are not visible when the Trend background colour is changed
- Data Export: When percentage n is used with absolute paths no data is exported
- Data Export: CSV file extension and launch Excel option for Data Export
- Data Export: Exporting to CSV with commas in regional settings
- RTD Server: RTD Server stops updating when more than one client is connected
- Logger: Client logging logs data twice
- Logger: Logger averaging over slow logging rates
- Logger: LogByTag with database connections displays the channel number for the last tag and not the name
- PID: PID layout windows layout for different servers not saved correctly
- PID: PID does not allow for entry of channel
- OPC: OPC Client causes OPC Server to crash
- Modbus Master Driver: Modbus Master outputs read on first scan remain in error after recovery from a comms failure
- Modbus Master Driver: Modbus Master digital outputs require analog outputs to be defined in devcap
- Alarm Monitor/IE: Tag & Description are not displayed in Alarm Monitor running on Internet Client
- Alarm System: Alarm Mail Annunciator crashes on system enable
- Internet Server: Toolbars are not available in Internet Explorer under Vista
- Internet Client: Key Error on Data Export with Internet client
- User Library : OS Platform issues
- Drivers: Generic RS232 driver gives error "can't initialise device"
- Drivers: Second driver doesn't request an Unlock Code

Version 3.1 contains the following fixes/changes from V2.9

Changes

- No longer supported on Windows NT or Windows 95/98 Supports Windows 2000/XP and Windows 2003.
- ♦ Logging to SQL Access Oracle and OLE-DB databases
- ♦ Trending from SQL Access Oracle and OLE-DB databases
- ♦ Export from SQL Access Oracle and OLE-DB databases
- Alarm Value Trigger Logging
- ♦ Datascan/Dataweb device Selection on Installation
- Channel 8 Character Units and 15 Character Tags
- Visual Studio .NET Support
- ♦ Configuration History.doc
- System Enable and Disable Options
- ♦ HP Agilent and Wokogawa WT Power Meter Drivers
- Modbus Master over TCP
- Alarm System Re-configure and Local Times
- Saving History channels

- ♦ General Workgroup users registry access
- General Configuration Import crashes if there are problems with import file
- ♦ General Main Menu doesn't run on Windows 2003 Server
- Data Export Digit grouping symbol confuses comma delimited Data Export.
- ♦ Drivers Allen Bradley SLC-500 support
- ♦ Internet Server Slow Pan & Zoom on Trends with Internet Server
- ♦ Internet Server Running Config Mon in Internet Client values flash up then go to zero
- ♦ Channel Monitor displays Waiting indefinitely when using Mouse Wheel
- Trends Header text doesn't print from Trends
- ♦ Trends No data displayed on X-Y Trends until scan buffer is increased
- ♦ Trends draws trend incorrectly if initial value is out of range
- ◆ Trends Can't be launched from Desktop
- ♦ Config Mon Auto calibrate from configurable monitor displays value in error
- ♦ Logger Config looses Logged Channels when service stop and LogByTag on

Version 2.9 contains the following fixes/changes from v2.7.2

Changes

- Excel RTD (Real Time Data) Server
- ♦ Generic RS-232 Driver Modem Control and Digital Text Output
- MSL Dataweb Control Centre Driver
- User Library Write Log Text Function
- Trends Channel : Pan Zoom, Text Tracks and Control Limits
- Trends Select "Next" or "Prev" Log File
- Channel values in logger text and file names

Bug Fixes

- ♦ Main Server Setup DDE Error Message on XP
- ♦ Main Export Configuration only allows 2 digits in channel range box
- ♦ Configurable Monitor ValueEntryHandles
- ♦ Channel Monitor Long Device Names
- Logger Analog Strings in Logger Directory
- Calculator Min function does not compile after 2.4
- Calculator Calculator Unary Minus after Bracket
- ◆ Data Export Elapsed Time Titles
- Data Export Data Export of Values greater then 1000
- ♦ Data Export Digital Values and Statistics Columns Alignment
- ♦ Alarm System Multiple Alarms Annunciation on System Enable
- Data Exchange Reading static OPC Values from Omniflex OPC server
- ♦ Data Exchange Network DDE problems
- Drivers Imp 10V range support
- Drivers Modbus Slave Diagnostics
- Drivers Modbus Slave Error Response
- Drivers SAIA Master on Fast Processors